

Ventilated | Low speed | Benchtop DST-6M



A VAL





• 0

Product Features

Product Overview

USER-FRIENDLY FUNCTIONS

meet dierent centrifugal requirements

>12 user-dened programs >19 rates acceleration and deceleration >1m to 9999min59s timer range >LCD screen shows all parameters simply and clearly >RCF can be set directly >RPM and RCF cove automatically >User can reset parameters when rotor is spinning

DST-6M is a non-refrigerated large capacity centrifuge with a maximum capacity of 2L, which suitable with 0.2mL-500mL tube/bottle,standard blood tube and microplate.

Also provide the rotor with biosafety cap for choice, can

ENSURE SAFETY

>Microprocessor control >Imbalance detection by three axis gyroscope ¢rifugation stop with display of error >Motorized electronic door lock >Door cannot be opened when rotor is spinning >Gas hinge to prevent door falling >Po in the door for calibration and operation checking >Emergency door lock release

GOOD COMPONENTS

>Motor: Variable frequency motor. stable running, maintenance free, long life >Housing: Thick and strong steel >Chamber: Food grade 304 stainless steel. anticorrosion and easy to clean >Rotor: Aluminum alloy xed angle rotor; Steel/Stainless steel swing out rotor. >Rotors are autoclavable

Model	TD-6M
Max speed	6000rpm
Max RCF	5200xg
Max capacity	4x50ml
Timer range	1s to 99h59m59s

	·
	ine Cart
61889	
	CPRA L

Speed accuracy	±10rpm
Noise	≤60dB(A)
Power consumption	500w
Dimension	495x400x310mm
Net weight	25kg





AVAILABLE ROTORS DST-6M

No.1

No.2



Order No.:10000401000 Rotor: Swing out rotor Capacity: 4×100ml Max speed: 5000rpm Max RCF: 4650×g Tube size: Ф38×114mm



Order Ne.:10000400500 Rotor: Swing out rotor Capacity: 4×50ml Max speed: 5000rpm Max RCF: 4650×g Tube size: Φ30×116mm

No.3

No.2



Order No.:10003200150 Rotor: Swing out rotor Capacity: 32×15ml Max speed: 4000rpm Max RCF: 2980×g Tube size: Φ17×121mm

а

d a

р

t

е

r



Order No.:10000800500 Rotor: Swing out rotor Capacity: 8×50ml Max speed: 4000rpm Max RCF: 2980×g Tube size: Φ30×116mm

Capacity

8×50ml

4×100ml

36×10ml

40x7ml blood tube

20×15ml



Order No.:10000801000 Rotor: Swing out rotor Capacity: 8×100ml Max speed: 4000rpm Max RCF: 2980×g Tube size: Ф38×114mm



Order No.:10004800077 Rotor: Swing out rotor Capacity: 48×2~7ml Isood tube Max speed: 4000rpm Max RCF: 3100×g Tube size: Φ13×75~100mm



Order No.:10000600024 Rotor: Microplate rotor Capacity: 2×3×96 well plate Max speed: 4000rpm Max RCF: 1970×g max: 128×87×60mm



Order No.

10200800502

10202000150





Order No.:10006400077

Rotor: Swing out rotor

Max speed: 4000rpm

Max RCF: 3100×g

Capacity: 64×2~7ml blood tube

Tube size: Φ13×75~100mm

Order No.:10000405000

Rotor: Swing out rotor Capacity: 4×500ml Max speed: 4000rpm Max RCF: 3400×g Tube size: Φ80×137mm



Order No.:10004000150 Rotor: Swing out rotor Capacity: 40×15ml Max speed: 4000rpm Max RCF: 3400×g Tube size: Φ17×121mm



Order No.:10000402500

Rotor: Swing out rotor

Max speed: 5000rpm

Tube size: Ø63×111mm

Capacity: 4×250ml

Max RCF: 5200×g

Order No.:10201600500(normal) Order No.:10201600501(aerosol tight) Adapter in 4*500ml(normal) Adapter in 4*500ml(aerosol tight) Capacity: 16×50ml Max RCF: 3400×g Tube size: Ф29×116mm



Order No.:10008000107 Rotor: Swing out rotor Capacity: 80×10ml blood tube Max speed: 4000rpm Max RCF: 3400×g Tube size: Φ15×100mm



order No.:10203600150(normal) order No.:10203600151(aerosol tight) Adapter in 4*500ml(normal) Adapter in 4*500ml(aerosol tight) Capacity: 36×15ml Max speed: 4000rpm Max RCF: 3400×g Tube size: Ф17×121mm



Order No.:10011200077 Rotor: Swing out rotor Capacity: 112×2~7ml blood tube Max speed: 4000rpm Max RCF: 3400×g Tube size: Ф13×75~100mm



No.6

Order No.:10101200150 Rotor: Fixed angle rotor Capacity: 12×15ml Max speed: 6000rpm Max RCF: 5120×g Tube size: Ф17×121mm



Order No.:10002000500

Rotor: Swing out rotor Capacity: 20×50ml Max speed: 4000rpm Max RCF: 3400×g Tube size: Ф29.5×116mm



Order No.:10014800050 Rotor: Swing out rotor Capacity: 148×5ml RIA tube Max speed: 4000rpm Max RCF: 3400×g Tube size: Ф13×75~100mm




Order No.:10100600500 Rotor: Fixed angle rotor Capacity: 6×50ml Max speed: 6000rpm Max RCF: 5120×g Tube size: Φ29×116mm

Order No.:10000800024 Rotor: Microplate rotor Capacity: 4×2×96 well plate Max speed: 4000rpm Max RCF: 3400×g

max: 128×87×60mm



Order No.:10000402502 Rotor: Swing out rotor Capacity: 4x250ml concal botto Max speed: 4000rpm Max RCF: 3400×g Tube size: Φ60×164mm



Max speed: 4000rpm Max RCF: 3400xg Tube size: Ф13×75~100mm



Rotor: Swing out rotor Capacity: 100×1.5ml Max speed: 4000rpm Max RCF: 3400×g Tube size: Ф11×42mm

No.5



Order No.:10009600077 Rotor: Swing out rotor Capacity: 96×2~7ml blood tube Max speed: 4000rpm Max RCF: 3400×g Tube size: Φ13×75~100mm