


# DSI500T pH/Ion Meter



## ❑ GENERAL FEATURES

- ✧ Color High contrast LCD touchscreen, 7.0 inches.
- ✧ Intelligent operation system provides features including user management, calibration management, method management, data management and etc.
- ✧ Multi-reading feature allows auto-read, timed-read and continuous-read.
- ✧ Automatic/Manual temperature compensation ensures accurate results.
- ✧ Data Storage 1000 sets for each parameter (GLP-compliant).
- ✧ Data analysis feature helps user review, compare and recalculate results.
- ✧ Support for USB or RS-232 communication.
- ✧ Reset feature automatically resumes all settings back to factory default options.
- ✧ IP54 waterproof.

## ❑ pH

- ✧ 1-6 points calibration with Standard Recognition.
- ✧ Selectable pH buffer groups, including DIN, NIST, USA, MERK, JIS, GB.
- ✧ Support for pH standard group customization.
- ✧ Automatic electrode diagnosis with pH slope and offset display.

## ❑ Ion

- ✧ 1-6 points calibration
- ✧ Selectable measurement unit, including  $\mu\text{g/L}$ ,  $\text{mg/L}$ ,  $\text{g/L}$ ,  $\text{mmol/L}$ ,  $\text{pX}$ ,  $\text{ppm}$ ,  $\text{ppb}$ , etc.
- ✧ Multi-measurement modes are supported, including Direct Reading mode, Standard Addition mode, Sample Addition mode and GRAN mode.
- ✧ Over 10 methods are built-in, including  $\text{F}^-$ ,  $\text{Cl}^-$ ,  $\text{Br}^-$ ,  $\text{I}^-$ ,  $\text{NO}_3^-$ ,  $\text{BF}_4^-$ ,  $\text{NH}_4^+$ ,  $\text{K}^+$ ,  $\text{Na}^+$ ,  $\text{Ca}^{2+}$ ,  $\text{Cu}^{2+}$ ,  $\text{Pb}^{2+}$ ,  $\text{Ag}^+$  and etc., user-defined method is supported.

## ❑ INCLUDES

- ✧ JB-10 stirrer
- ✧ REX-5 electrode stand



# DSI500T pH/Ion Meter

## PRODUCT SPECIFICATIONS

Model		DSI500T
Parameters		pH/ISE/Temp.(mV/ORP/pX)
pH	Range	-2.000 to 20.000 pH
	Resolution	0.1, 0.01, 0.001pH
	Accuracy	$\pm 0.002$ pH
	Calibration Points	Up to 6
	Standard Customization	Yes
	Calibration Reminder	Yes
	Standard Recognition	NIST, GB, DIN, USA, MERK, JIS buffers
	Slope Limit	Yes
mV/ORP	Range	-2000.00 to 2000.00 mV
	Resolution	0.1, 0.01 mV
	Accuracy	$\pm 0.1$ mV or $\pm 0.03\%$
	EH ORP Mode	Yes
	ORP Calibration Points	1 custom point (relative mV)
pX	Range	-2.000 to 20.000 pX
	Resolution	0.1, 0.01, 0.001 pX
	Accuracy	$\pm 0.002$ pX
	Calibration Points	Up to 6
ISE	Range	1.000e-9 to 9.999e+9
	Units	mol/L, mmol/L, g/L, mg/L, $\mu\text{g/L}$ , ppm, ppb
	Resolution	Up to 4 significant digits
	Accuracy	$\pm 0.3\%$
	Calibration Points	Up to 6
Temperature	Range	-10 to 135 $^{\circ}\text{C}$ , 14 to 275 $^{\circ}\text{F}$
	Unit	$^{\circ}\text{C}$ , $^{\circ}\text{F}$
	Resolution	0.1
	Accuracy	$\pm 0.1^{\circ}\text{C}$
Measurement	Reading Mode	Auto Read (Fast, Medium, Slow), Timed, Continuous
	Reading Prompts	Reading, Stable, Locked
	Temp. Compensation	ATC, MTC
Data management	Data Storage	1000 Groups
	GLP Features	Yes
	Log Management	Yes
Inputs	pH Electrode	BNC(Q9)
	Temp. Probe	4-pin aviation connector
Outputs	USB	USB 2.0 flash memory device, PC, scanner
	RS 232	printer, auto-sampler
Display options	Backlight	Yes
	Auto Shutdown	1~60 min, off
	IP Rating	IP54
	Date and Time	Yes
General	Power	AC Adapter, 100-240V AC input, DC24V output
	Dimensions	220 $\times$ 195 $\times$ 68 mm
	Net Weight	950g (2.09 lb)
	Dimensions (Carton)	370 $\times$ 305 $\times$ 330 mm
	Shipping Weight	6.5 kg