



PH

pH/Ion Meter



India Office

16 S/F B/S, T-Block Extn.
Jain Colony Part-2 Uttam Nagar,
New Delhi-110059
info@darsunscientific.in
(+91) 9999136670, 7835864003

Australia Headquarters

21b Lawler Drive, Oran Park, NSW,
2570, Australia
info@darsunscientific.com
+61-283135514, 430583632

DarsunScientific



Darsun Scientific

pH/Ion

Meter

DSI300F



ph

1-5 points calibration with Standard Recognition.
Selectable pH buffer groups, including NIST, DIN, GB, USA.
Automatic electrode diagnosis with pH slope and offset display.

INCLUDES

JB-10 stirrer
REX-5 electrode stand

GENERAL FEATURES

- High resolution LCD display, 5.7 inches.
- Multi-reading feature allows auto-read, timed-read and continuous-read.
- Automatic/Manual temperature compensation ensures accurate results.
- Auto-hold feature senses and locks the measurement endpoint.
- Data Storage 500 sets (GLP-compliant).
- Support for USB or RS-232 communication.
- Reset feature automatically resumes all settings back to factory default options.
- IP54 waterproof.

Ion

- 1-5 points calibration.
- Selectable measurement unit, including $\mu\text{g/L}$, mg/L , g/L , mmol/L , pX , ppm , ppb , etc.
- Multi-measurement mode is supported, including Direct Reading mode.
- Over 10 methods are built-in, including F^- , Cl^- , Br^- , I^- , NO_3^- , BF_4^- , NH_4^+ , K^+ , Na^+ , Ca^{2+} , Cu^{2+} , Pb^{2+} , Ag^+ and etc., user-defined method is supported.

Model	DSI300F	
Parameters	pH/ISE/Temp.(mV/pX)	
pH	Range	-2.00 to 20.00 pH
	Resolution	0.1, 0.01 pH
	Accuracy	± 0.01 pH
	Calibration Points	Up to 5
	Standard Customization	Yes
	Standard Recognition	NIST, GB, DIN, USA buffers
mV	Range	-2000.0 to 2000.0 mV
	Resolution	0.1 mV
	Accuracy	± 0.3 mV or $\pm 0.1\%$
pX	Range	-2.00 to 20.00 pX
	Resolution	0.1, 0.01 pX
	Accuracy	± 0.01 pX
	Calibration Points	Up to 5
ISE	Range	1.000e-9 to 9.999e+9
	Unit	mol/L, mmol/L, g/L, mg/L, $\mu\text{g/L}$, ppm, ppb
	Resolution	Up to 4 significant digits
	Accuracy	$\pm 0.3\%$
	Calibration Points	Up to 5
Temperature	Range	-5.0 to 110 °C, 23.0 to 230 °F
	Unit	°C, °F
	Resolution	0.1
	Accuracy	$\pm 0.2^\circ\text{C}$
Measurement	Reading Mode	Auto Read (Fast, Medium, Slow), Timed, Continuous
	Reading Prompts	Reading, Stable, Locked
	Temp. Compensation	ATC, MTC
Data management	Data Storage	500 results each
	GLP Features	Yes
Inputs	pH Electrode	BNC(Q9)
Outputs	Temp. Probe	4-pin aviation connector
Display options	USB	PC
	RS 232	printer
	Backlight	Yes
	Auto Shutdown	1-60 min, off
General	IP Rating	IP54
	Date and Time	Yes
	Power	AC Adapter, 100-240V AC input, DC9V output
	Dimensions	242×195×68 mm
	Net Weight	900g (1.98 lb)
	Dimensions (Carton)	370×320×220 mm
	Shipping Weight	3.5 kg