



2°C~8°C Pharmacy Refrigerator

Contact Us

Darsun Scientific India Pvt Ltd

16 S/F B/S, T-Block Extn. Jain Colony Part-2 Uttam Nagar,
New Delhi-110059

Email: info@darsunscientific.in

Mob: (+91) 9999136670, 7835864003

Web: <https://darsunscientific.in/>

Head office

Darsun Scientific Australia Pty Ltd.






21b Lawler Drive, Oran Park, NSW, 2570, Australia

Email: Info@darsunscientific.com

Tel- +61-283135514

Contact- +61-430583632

www.darsunscientific.com

Model					
	DS-4L395	DS-4L525	DS-4L650	DS-4L725	DS-4L1015
Performance					
Temperature range	2~8℃				
Ambient Temperature	16~32℃				
Cooling Performance	5℃				
Climate Class	N				
Controller	Microprocessor				
Display	Digital display				
Cabinet Type	Upright				
Capacity (L)	395	525	650	725	1015
Internal Size(W*D*H)mm	580x533x1352	610x685x1264	605x725x1515	980x595x1260	1070x670x1515
External Size(W*D*H)mm	650x673x1992	720x810x1961	715x890x1985	1093x718x1992	1180x852/900x1990
Package Size(W*D*H)mm	717x732x2065	775x868x2130	773x947x2153	1187x795x2136	1313x988x2168
NW/GW(Kgs)	95/120	141/178	157	171/208	223/297
Refrigeration					
Compressor	1pc				
Cooling Method	Air cooling				
Defrost Mode	Automatic				
Refrigerant	R600a	R290			
Insulation Thickness(mm)	R/L:35,B:52	L/R:55,B:55	55	L/R:55,B:55	L/R/B:55
Construction					
External Material	PCM				
Inner Material	HIPS	Aluminum plate with spraying /stainless steel (optional)			
Shelves	6+1(coated steel wired shelf)	6 (coated steel wired shelf)	5(coated steel wired shelf)	12 (coated steel wired shelf)	
Door Lock with Key	Yes				
Lighting	LED				
Padlock	YES	-			
Access Port	1pc. Ø 25 mm				
Casters	4+ (2 leveling feet)	4(2 leveling feet)		4+ (2 leveling feet)	
Data Logging/Interval/Recording Time	USB/Record every 10 minutes / 2 years				
Door with Heater	Yes				
Alarm					
Temperature	High/Low temperature, High ambient temperature, Condenser overheating				
Electrical	Power failure , Low battery				
System	Sensor failure, Door ajar Built-in USB data logger failure, Communication failure				
Electrical					
Power Supply(V/HZ)	220-240~/50	220-240~/50	220-240~50/60	220-240~/50	220-230~/50
Rated Power(W)	252	310	430	540	520
Power Consumption(KWh/24h)	3	3.65	4.73	8.42	8.24
Rated Current(A)	1.8	2.49	3.06	3.90	3.21
Accessories					
Standard	RS485, Remote alarm contact, Backup battery				
Options	Printer		Printer, RS232, Chart Recorder	Printer	

Real Air Cooling

The multi-duct vortex refrigeration system and finned evaporator can prevent frosting completely and improve temperature uniformity to a large extent..

Real Energy Saving

The refrigerator is equipped with "M + Energy Core" power management system and complete air cooling design, improving energy saving efficiency by more than 40%.

Real Visibility

The electrical heating + LOW-E design with double considerations can achieve a better anti-condensation effect for the glass door.

Real Safety

Seven temperature probes can ensure high precision of temperature control with nearly no fluctuation and thus can improve safety..




Performance Data / Cooling Curve

— Cooling — Air Temp
Refrigerator Cooling — Freezer Cooling — Air Temp —

DS-395L




DS-525L




DS-650L




DS-725L




DS-1015L




DS-395L




DS-525L




DS-650L



DS-725L



DS-1015L





Refrigeration System

Equipped with a compressor supplied by an international famous brand, high-efficiency air-cooled condenser and finned evaporator, ensuring fast refrigeration.



Intelligent Temperature Control

- Equipped with high-precision microcomputer temperature control system and 1 high-brightness digital temperature display with display accuracy at 0.1°C.
- Equipped with a remote alarm access port and 485 data access port.



Security System

- The well-developed audible & visual alarm system with multiple audible & visual alarm functions: high temperature alarm, low temperature alarm, sensor failure alarm, door ajar alarm, power failure alarm;
- The turn-on delay and stopping interval protection function can ensure reliability in running;
- The door is equipped with a lock, preventing it from opening accidentally.



Data Storage

- Equipped with a USB export interface, which can be used for exporting data in PDF;
- When a U-disk is connected, temperature data can be stored continuously and automatically (data can be stored for 100,000 sets of data);
- The printer is optional.



Human-oriented

- Equipped with high-quality shelves made from PVC-coated steel wire with tag cards and classification marks, which are easy to clean;
- Upgrade with aluminium alloy door handle, ensuring elegance of appearance;
- Equipped with testing port, bringing convenience to users in testing temperature inside the cabinet.