



ORBITAL SHAKER / DESIGNED FOR CO2 INCUBATORS



India Office

16 S/F B/S, T-Block Extn.
Jain Colony Part-2 Uttam Nagar,
New Delhi-110059
info@darsunscientific.in
(+91) 99999136670, 7835864003

Australia Headquarters

21b Lawler Drive, Oran Park, NSW,
2570, Australia
info@darsunscientific.com
+61-283135514, 430583632

DarsunScientific



Darsun Scientific

ORBITAL SHAKER / DESIGNED FOR CO2 INCUBATORS

DS-26M



Features

- Remote Control attaches externally to CO2 Incubator
- LED display shows both set and actual parameters without opening the door
- Simple and intuitive design provides easy operation
- Alarm function alerts the user when the timer reaches zero
- Shaker is easy to remove for cleaning/disinfecting to protect your cells
- The Magnetic Orbital Drive system uses magnetic force to deliver precise speed control, low vibration, maintenance free operation and long service life
- Suitable for use in CO2, Standard or Refrigerated Incubators at up to 20% CO2 and 90% Humidity environments
- Wide range of accessories to accommodate various sample holders

MODEL	DS-26M
Orbital Diameter	ø19 mm (0.75 in)
Speed	30–300 rpm
Timer	00:00–99h:59min ("0" for running continuously)
Platform Dimensions	305 × 360 mm (12 × 14.2 in)
Max Flask Capacity	30 × 25/50 ml; 15 × 100/150/200/250 ml; 9 × 500 ml; 6 × 1000 ml; 4 × 2000 ml; 2 × 3000 ml; 1 × 5000 ml
Max. Load	6 kg (13.2 lbs)
Operating Environment	Ambient Temperature: 5°C – 60°CRelative Humidity: ≤95%
Max. Power	8.5 W
Power Supply	AC 100–240 V, 50 Hz / 60 Hz
Net Weight	18 kg (37 lbs)
Shaker Dimensions	375 × 300 × 94 mm (14.8 × 11.8 × 3.7 in)
Control Box Dimensions	90 × 160 × 26 mm (3.5 × 6.3 × 1.02 in)