



# PH pH Meter



#### India Office

16 S/F B/S, T-Block Extn.  
Jain Colony Part-2 Uttam Nagar,  
New Delhi-110059  
info@darsunscientific.in  
(+91) 9999136670, 7835864003

#### USA Headquarters

30 N Gould St, Ste R  
Sheridan, Wyoming 82801  
United States

**Darsun**Scientific

Darsun Scientific

# pH Meter

## DS110B

- E-201F pH composite electrode
- NIST pH standard solution(4.01, 7.00, 10.01) , 50ml/vial
- Electrode holder
- Silicone rubber case
- Wristbands



- LCD display screen, 3.5 inches.
- Reset feature automatically resumes all settings back to factory default options.
- Auto-power off feature effectively extends the battery service life.
- IP65 waterproof. The portable meter is suitable for fields measurements and out door measurements.
- 1-2 points calibration with Standard Recognition.
- Manual temperature compensation ensures accurate results

Model		DS110B
Parameters		pH/mV
pH	Range	-0.00 to 14.00pH
	Resolution	0.01pH
	Accuracy	±0.03 pH
	Calibration Points	Up to 2
mV	Auto Standard Recognition	NIST buffers
	Range	-1400.0 to 1400.0 mV
	Resolution	1 mV
Measurement	Accuracy	±0.2%FS
	Reading Mode	Continuous
	Reading Prompts	Reading, Stable
	Temp. Compensation	MTC
Inputs	pH Electrode	BNC(Q9)
Display options	Backlight	Yes
	Auto Shutdown	300, 600, 1200, 1800, 3600 sec., off
General	IP Rating	IP65
	Power	Rechargeable Lithium battery, AC Adapter, 100-240V AC input, DC5V output
	Dimensions	80×225×35 mm
	Net Weight	400g (0.88 lb)
	Dimensions (Carton)	300×290×140 mm
	Shipping Weight	1kg