



India Office
16 S/F B/S, T-Block Extn.
Jain Colony Part-2 Uttam Nagar,
New Delhi-110059
info@darsunscientific.in
(+91) 9999136670, 7835864003

USA Headquarters
30 N Gould St, Ste R
Sheridan, Wyoming 82801
United States

Darsun Scientific

Sample Homogenizer



DS-6



DS-6 sample Homogenizer is a small size lab instrument, suit for various of samples grinding. Touch screen display, easy to operate: High speed, brings as high efficiency. Commonly used for sample pretreatments in industries of biology, chemistry, pharmacology, minerals, medicine, etc

Specification

- Enhanced motor, high quality bearing, touch screen
- High efficiency grinding, stable working, low noise
- Extensive speed range, custom and preset programs
- Transparent lid with protection, easy to use
- Double-position operation

Model	DS-6			
Speed range	2450rpm-4450rpm	Deceleration time		2s
Sample capacity	6*2ml /2*5ml	Grinding method		Dry, Wet
Feed size	According to tube size	Adapter material		POM/Nylon
Final fineness	~5μm	Safety security		Immediate stop once lid open
Grinding beads diameter	0.1-5mm	Voltage		AC100-240V 50/60Hz
Acceleration time	2s	Dimension (W×D×H)		351mmX215mmX202mm
Power	250W			
Adapter type	Picture	Tube type	Capacity	Material
For 5ml tubes			1	pc
For 2ml tubes			3	pc