



TABLE TOP STEM STERILIZER



India Office

16 S/F B/S, T-Block Extn.
Jain Colony Part-2 Uttam Nagar,
New Delhi-110059
info@darsunscientific.in
(+91) 9999136670, 7835864003

USA Headquarters

30 N Gould St, Ste R
Sheridan, Wyoming 82801
United States

DarsunScientific

DARSUN
SCIENTIFIC

Darsun Scientific

TABLE TOP STEM STERILIZER

DS-T-18B/DS-T-23B
DS-T-45B



Product Overview

- 1-Automatic door switch
- 2-Automatic water
- 3-Quality stainless steel inner tank sealed cover
- 4-Microcomputer control
- 5-Safety interlocking device
- 6-With drying function
- 7-With BD test HELIX test VACCUME test .
- 8-LED display and inductive operation
- 9-European CLASS B standard .
- 10-With automatic protection function : over temperature protection over pressure protection low water level protection anti dry burning safety door lock .
- 11-Three time per-vacuum
- 12-Buzzer reminder after sterilization . Automatic stop .
- 13-Automatic discharge of cold air . Automatic steam exhaust after sterilization .
- 14-Built-in steam generator to provide saturated steam quickly
- 15-With built-in printer USB function and U disk

Model	DS-T-18B	DS-T-23B	DS-T-45B
Volume	18L	23L	45L
Power	2 KW	2 KW	2.5 KW
Voltage	110V/220V,60HZ /50 HZ		
Design Pressure	0.25 MPA		
Temperature	139°C		
Rated working Pressure	0.22 MPA		
Rated working temperature	134°C		
Chamber volume	250X370	250X470	316X615
Outer Dimensions	620X505X450	505X710X450	980X750X630
Packing size (LxWxH)	670X560X510	760X560X510	980X570X630
Weight	62/53 (kg)	65/58 (kg)	142/105 (kg)