



Touch screen Double-line Printing sealing machine



India Office

16 S/F B/S, T-Block Extn.
Jain Colony Part-2 Uttam Nagar,
New Delhi-110059
info@darsunscientific.in
(+91) 9999136670, 7835864003

USA Headquarters

30 N Gould St, Ste R
Sheridan, Wyoming 82801
United States

DarsunScientific



Darsun Scientific

Touch screen Double-line Printing sealing machine

DS100-CC



Model	DS100-CC		
Control System	7" color LCD touch screen	Sealing Line Width	12mm
Cutting Length	>50mm	Temperature Deviation	<1%
Sealing Speed	10+0.5m/min	Work Temperature	60–220°C set arbitrarily
Function Type	Continuous sealing, automatic printing (Double-Line print), sealing counting		
Heat and Cool	Room temperature rises to 180°C in less than 40s, auxiliary cooling design		
Heating Method	Advanced flat heating element, can dry burn, high temperature resistance, long service life, high thermal efficiency		
Print Content	Sterilization date, expiration date, pot number, pot batch, operator, items, customized content, etc. Can print English, numbers and international symbols		
Historical Data Query	Historical data export function, USB data export function		
Replace the Ribbon	Convenient and fast		
Standby Function	Automatic energy-saving standby, standby time and temperature adjustable		
Safety Guarantee	the deviation between the sealing temperature and the set working temperature exceeds 4°C, it will automatically stop working		
Self-check Function	Automatic detection in working process, automatic alarm prompt in case of failure		
Operating System	Standard (Default) / Android		
Housing Style	Convex cover (Default) / Flat cover		
Housing Material	Carbon steel (Default) / Stainless steel		
Indentation Style	Flat wheel sealing (Default) / Single indentation sealing / Pattern wheel sealing		
WIFI	Optional: connect to the hospital traceability system via WIFI		
Voice Broadcast	Optional		