



WB WATER BATH POT



India Office

16 S/F B/S, T-Block Extn.
Jain Colony Part-2 Uttam Nagar,
New Delhi-110059
info@darsunscientific.in
(+91) 9999136670, 7835864003

USA Headquarters

30 N Gould St, Ste R
Sheridan, Wyoming 82801
United States

DarsunScientific

Darsun Scientific

WATER BATH POT

DS-2-4/DS-2-6/DS-2-8



DARSUN
SCIENTIFIC

Product Features

- Inner liner is made of stainless steel.
- Temperature control system adopted microcomputer chip processor, high precision temperature control.
- Easy to operate, with of functions such as timing setting, over-temperature alarm.
- Auxiliary menu for over-temperature alarm, to achieve deviation correction.
- Adjustable beaker hole.
- Touch button setting, with functions such as over-temperature alarm, relay protection, temperature correction, timing etc. timing range 0-999 minutes.
- Heating method: bottom heating, nature water convection heat transfer.
- Optional LCD meter (with start-stop function)

Model	DS-2-4	DS-2-6	DS-2-8
Name	Double rows four holes	Double rows six holes	Double rows eight holes
Power(KW)	1	1.5	2
Volume	12L	18.6L	22.6L
Temperature range	RT+5-100°C		
Temperature degree of fluctuations	±0.5°C		
Temperature degree of uniformity	±0.5°C		
Cooling method	Nature cooling		
Inner size(mm)	305x305x130	470x305x130	600x290x130
Appearance size(mm)	340x350x210	510x350x210	635x340x210
Power supply	220V/ 50Hz		