

ULT Freezer -40°C





Product Overview

Suitable for hospitals, blood banks, scientific research institutions, electronic lab and chemical lab, bioengineering as well as in the electronics and chemical industry

Construction

Inner made of electro galvanized steel with antimicrobial coating to prevent microbial growth. Exterior of powder coated galvanized steel

Main Feature

CFC- free technology
 CFC free refrigerant – R 290
 Electronic temperature controller
 Safety door lock
 Malfunction alarm
 LED lighting design
 Optional: Wireless temperature monitoring kit with SMS notification system

Temperature Control System

Microcomputer control, digital display of internal temperature accurate to 0.1°C, adjustable internal temperature -20 to -40°C

Safety

Various fault alarms: High/low temperature alarm, sensor fault alarm, open door alarm, power failure alarm, battery under voltage alarm etc
 Double door, 100mm thick insulation layer, double seal inside and outside
 Thermal insulation


Refrigeration

Fluoride-free refrigerant, green and environment friendly

Ergonomic design

Wide voltage design, 10 separate drawers, universal wheels and fixed feet, door frame heated

Cooling Curve



Basic	Model No	DS-40L525
	Cabinet Type	Vertical
	Basket	6/4
	Lock with key	Yes
Technical Parameter	Thermometer hole design	Yes
	Door	2
	Cooling Type	Direct Cooling
	Refrigerant	R404a
	Ground Clearance (mm)	100/128
	Automatic/manual defrost	Manual
	Power	310W
Temperature	Noise Level(db)	52
	Ambient temperature in which the freezer operates	10°C~32°C
Controller	Temperature Range (C)	-20~-40°C
	Temperature Controller	Electronic temperature controller
	Ambient temperature display	Yes
Electronic parameter	Sensor Type	PT100/PT1000
	Voltage / Frequency	220V/50Hz
Size	Capacity (L)	525
	Net/Gross Weight(Kg)	175/195 kg
	Outer Size (W*D*H)mm	945*861*1900mm
Alarm features	Inner Size (W*D*H)mm	684*612*1184mm
	High low temperature alarm-Buzzer alarm	Yes
	High low temperature alarm-Light alarm	Yes
	Sensor malfunction alarm-Buzzer alarm	Yes
	Sensor malfunction alarm-Light alarm	Yes
	Open the door alarm-Buzzer alarm	Yes
	Open the door alarm-Light alarm	Yes
Connectivity	Power failure alarm-Buzzer alarm	Yes
	Power failure alarm-Light alarm	Yes
	USB connection	Yes
	Battery backup for alarms (approx.72 hrs)	72 hours of power failure alarm, display the actual temperature in the box
Utility & certificates	Direct download of logged data on USB memory stick	Yes
	The control panel locking	Yes
	Castor	Universal wheels
Utility & certificates	Adjustable legs	2
	Certification	ISO 9001, CE Certified, FDA, IEC 60601-1 & IEC 61010-1